

**Amendments to the Claims:**

Please add new claim 25 as follows. This listing of claims will replace all prior versions and listings of claims in the application.

**Listing of Claims:**

1. (Previously Presented) A multi-beam light source unit comprising:
  - a laser diode unit for discharging a plurality of laser beams;
  - a rotational member for supporting the diode unit and rotating to a substantially aligned position between a plurality of the laser beams;
  - a fixing member for supporting the rotational member in a rotatable manner;
  - a temporary joining part for maintaining joining status between the rotational member and the fixing member such that the rotational member rotates under elastic force, wherein the elastic force is increased when the rotational member is rotated for position alignment between the plurality of the laser beams; and
  - a fixing part for fixing the rotated rotational member to the fixing member.
  
2. (Previously Presented) The unit according to claim 1, wherein the temporary joining part comprises:
  - a rotational boss installed in a projecting manner on a central part of the rotational member, the rotational boss comprising an outer periphery having a varied radius;
  - a boss cavity formed on the fixing member, for receiving the rotational boss in a rotatable manner; and
  - a plurality of elastic ribs on an inner periphery of the boss cavity for elastically supporting the outer periphery of the rotational boss at a plurality of positions.

3. (Previously Presented) The unit according to claim 2, wherein the temporary joining part further comprises:

the plurality of elastic ribs formed at substantially equal intervals on the inner periphery of the boss cavity; and

a plurality of holes for generating the elastic force on the elastic ribs formed, respectively, on an outer periphery of the plurality of elastic ribs.

4. (Original) The unit according to claim 3, wherein the plurality of elastic ribs comprises four elastic ribs.

5. (Original) The unit according to claim 3, wherein the temporary joining part further comprises:

a plurality of contact surface parts formed at a predetermined depth on a portion in the outer periphery of the rotational boss for contacting the plurality of elastic ribs, and wherein a predetermined interval is maintained between an inner periphery of the boss cavity rib and an outer periphery of the rotational boss, except between the elastic rib and the contact surface part.

6. (Original) The unit according to claim 1, wherein the laser diode unit comprises:

a multi-beam semiconductor laser diode having at least two laser beam discharging parts; and

an operation circuit board for controlling operation of this laser diode, and wherein the operation circuit board is joined to the rotational member.

7. (Original) The unit according to claim 1, wherein the fixing part comprises:

at least one screw for fastening the rotational member to the fixing member, and wherein the rotational member comprises an arc-shaped long slot through which the at least one screw passes.

8. (Original) The unit according to claim 7, wherein the fixing part further comprises a plurality of screws.

9. (Original) The unit according to claim 8, wherein the plurality of screws comprises two screws.

10. (Original) The unit according to claim 2, wherein the fixing member comprises:

- a first member comprising the boss cavity; and

- a second member vertically extended from the first member and having a settle unit and a pair of fixing parts.

11. (Original) The unit according to claim 10, further comprising:

- a collimating lens for converting a plurality of laser beams discharged from the laser diode unit into a parallel light; and

- a lens holder for fixing the collimating lens, and wherein the lens holder is adapted to be settled down on the settle unit of the second member.

12. (Previously Presented) A multi-beam laser scanning unit comprising:

- a multi-beam light source unit for discharging a plurality of laser beams;

- a scanning/image resulting unit for forming an image on a scanned surface by scanning the plurality of laser beams;

- a frame for supporting the multi-beam light source unit and the scanning/image resulting unit, wherein the multi-beam light source unit comprises:

- a laser diode having at least two laser beam discharging parts;

- an operation circuit board for controlling operation of the laser diode;

- a rotational member for supporting the laser diode and the operation circuit board, and rotating to a substantially aligned position between a plurality of the laser beams;

a fixing member for supporting the rotational member in a rotatable manner;

a temporary joining part for maintaining joining status between the rotational member and the fixing member such that the rotational member rotates under elastic force, wherein the elastic force is increased when the rotational member is rotated for position alignment between the plurality of the laser beams; and

a fixing part for fixing the rotated rotational member to the fixing member.

13. (Original) The unit according to claim 12, wherein the multi-beam light source unit is fixed and installed in a bottom wall of the frame.

14. (Previously Presented) The unit according to claim 13, wherein the scanning/image resulting unit comprises:

a polygon mirror for scanning a plurality of laser beams discharged from the multi-beam light source unit;

an image resulting lens for causing the laser beam scanned by the polygon mirror to impinge onto the scanned surface;

a cylindrical lens for linearly condensing a plurality of the laser beams on a reflection surface of the polygon mirror; and

a synchronization signal detecting unit.

15. (Previously Presented) The unit according to claim 13, wherein the temporary joining part comprises:

a rotational boss installed in a projecting manner on a central part of the rotational member, the rotational boss comprising an outer periphery having a varied radius;

a boss cavity formed on the fixing member, for receiving the rotational boss in a rotatable manner; and

a plurality of elastic ribs on an inner periphery of the boss cavity for elastically supporting the outer periphery of the rotational boss at a plurality of positions.

16. (Previously Presented) The unit according to claim 15, wherein the temporary joining part further comprises:

the plurality of elastic ribs formed at substantially equal intervals on the inner periphery of the boss cavity; and

a plurality of holes for generating the elastic force on the elastic ribs, the holes formed on respective portions of an outer periphery of the plurality of elastic ribs.

17. (Original) The unit according to claim 16, wherein the plurality of elastic ribs comprises four elastic ribs.

18. (Original) The unit according to claim 16, wherein the temporary joining part further comprises:

a plurality of contact surface parts formed at a predetermined depth on a portion in the outer periphery of the rotational boss for contacting the plurality of elastic ribs, and wherein a predetermined interval is maintained between an inner periphery of the boss cavity and an outer periphery of the rotational boss except between the elastic rib and the contact surface part.

19. (Original) The unit according to claim 12, wherein the fixing part comprises:

at least one screw for fastening the rotational member to the fixing member, and wherein the rotational member has an arc-shaped long slot through which the at least one screw passes.

20. (Original) The unit according to claim 19, wherein the fixing part further comprises the at least one screw comprising a plurality of screws.

21. (Original) The unit according to claim 20, wherein the plurality of screws comprises a pair of screws.

22. (Original) The unit according to claim 13, wherein the fixing member comprises:

a first member having the boss cavity; and

a second member vertically extended from the first member and having a settle unit and at least one fixing part.

23. (Original) The unit according to claim 22, wherein the multi-beam light source unit further comprises:

a collimating lens for converting a plurality of laser beams discharged from the laser diode unit into a parallel light; and

a lens holder for fixing the collimating lens, and wherein the lens holder is settled down on the settle unit of the second member.

24. (Original) The unit according to claim 22, wherein the at least one fixing part comprises a pair of fixing parts.

25. (New) A multi-beam light source unit comprising:

a laser diode unit for discharging a plurality of laser beams;

a rotational member for supporting the diode unit, said rotational member having a boss; and

a fixing member for supporting the rotational member in a rotatable manner,

wherein said fixing member includes a boss cavity and a plurality of elastic ribs on an inner periphery of the boss cavity for elastically supporting the outer periphery of the boss at a plurality of positions.